



## IPC-STAN-9301IRV

3 Megapixel Camera

### OVERVIEW

Having 3 megapixel real-time resolution and high quality optics makes the IPC-STAN-9301IRV suitable for applications where precision matters. The Camera has built-in IR LEDs providing illumination up to 50 meters, and its staggering 140dB Wide Dynamic Range ensures a clear quality image, even on bright backlit scenes.

The camera is IP67 outdoor ready, and its IK10 rating makes it suitable for installation where robustness is a must. It also has micro SD card slot available for edge storage.

All Stanley Cameras utilize H.264 or 265 compression with dual-streaming, reducing bandwidth load. Supported ONVIF open communication standard makes them compatible with multiple recording platforms including Milestone, Genetec, Mirasys, Lenel, etc.

### STANDARD FEATURES

- 1/2.8" 3 Megapixel CMOS
- H.265 & H.264 triple-stream encoding
- 25fps@3MP(2048x1536)
- Ultra Wide Dynamic Range up to 140dB
- Ultra 3D DNR, AWB, AGC, BLC
- Ultra Defog, ROI, EIS
- 2.8 – 12mm motorized lens
- 50m IR Illumination, Smart IR
- Smart detections: Tripwire, Intrusion, Object Abandoned/Missing
- Intelligent functions: People counting, Heat map
- Multiple network monitoring: Web viewer, Stanley Video Viewer Desktop & Mobile
- IP67, IK10, PoE, Micro SD memory



<b>Camera</b>	
<b>IPC-STAN-9300IRV</b>	
Image Sensor	1/2.8" 3Megapixel CMOS
Effective Pixels	2048(H)x1536(V)
Scanning System	Progressive
Min. Illumination	Color: 0.005 Lux/F1.4, B/W: 0Lux/F1.4(IR on)
S/N Ratio	More than 50dB
IR On/Off Control	Auto/Manual
IR LED Range	50m, Smart IR technology
<b>Lens</b>	
Focal Length	2.8 – 12mm
Max Aperture	F1.4
Focus Control	Motorized
Angle of View	H: 87°(Wide) ~31°(Tele)
Lens Type	Motorized/Auto Iris(DC)
Mount Type	Board-in Type
Close Focus Dist.	0.3m
<b>Video</b>	
Compression	H.265 / H.264 / MJPEG
Resolution	3M(2048x 1536)/1080P / 720P / D1 / (640x360) / CIF
Frame Rate	Main Stream 3M/1080P/720P(1~25fps) Sub Stream D1/CIF(1~25fps) Third Stream 1080P/720P/D1/640x360(1~25fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 40K ~ 10Mbps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC / HLC / WDR (140dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion detection	Off / On (4 Zone, Rectangle)
ROI	Up to 4 areas
Zoom	4x Optical / 16x Digital
Flip	0°/90°/180°/270°
Privacy Masking	Up to 4 areas

<b>Intelligence</b>	
Smart detection	Tripwire
	Intrusion
	Missing/Abandoned
	Scene change
	Audio detect
Intelligence	Face detect
	People counting
	Heat map
<b>Audio</b>	
Compression	G.711a /G.711u/AAC
<b>Network</b>	
Ethernet	RJ-45 (100/1000Base-T)
Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
Compatibility	ONVIF, PSIA, CGI
Edge Storage	NAS, Micro SD card 128GB
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android
<b>Auxiliary Interface</b>	
Audio	1/1 channel In/Out
Alarm	2/1 channel In/Out
<b>General</b>	
Power Supply	AC24V/DC12V, PoE(802.3af)
Power Consumption	<12W
Working Environment	-40°C~+60°C, Less than 90% RH
Ingress Protection	IP67
Vandal Resistance	IK10
Dimensions	Φ159.1mm x 117.9mm
Weight	0.89kg Net / 1.13kg Gross
<b>Certifications</b>	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B
<b>Accessories</b>	
Junction box	PFA138
Pole mount	PFA152
Wall mount	PFB302S + PFA101
Pipe mount	PFB300C + PFA101
In-ceiling mount	PFB201C